

**Shortwave Infrared Paint
Curing System**

Instruction Manual

Model No: FY-2W



Shortwave Infrared Paint Curing Lamp

INSTRUCTION MANUAL

*Please read this manual carefully before installing or servicing this equipment.

Precaution


1. This equipment is designed for paint curing applications. Keep a safe distance between emitter and panel. Improper servicing can cause paint surface damage.
2. Installation and service must be performed by a qualified installer or service agent.
3. The system has been designed for easy installation, low operating costs and minimal maintenance. The warranty does not cover lamp tube defects resulting from misuse or improper operation.
4. Disconnect from power source when the equipment not in use for a long period.
5. The lamp tube should not be perpendicular to the ground when the equipment is operating. Otherwise, it will shorten the life of the lamp tube.
6. Turn off the equipment after using. Place the equipment in a safe place to avoid damage to the lamp tube.

Technical Parameter


Model Parameter	FY-2W
Power Supply	220V 50/60Hz Single Phase
Input Power	2 × 1100W
Curing Area	800×800mm
Temperature	40°C – 75°C
Timer	0min-60min Adjustable
Light intensity	100%

Installation

Able to move upwards, downwards and rotate 360°



Controls



Operation

1. Set curing time according to the requirements of paint for curing.
2. To achieve the best results, the emitters should be parallel with the paint surface. Keep a distance of 30-60cm from the panel.
3. During the process of curing, the paint surface must be clean without water and impurities.
4. Switch on the power supply and set up the curing time to start curing process.
5. Turn off the equipment after using. Place the equipment in a safe place to avoid damage to the lamp.